

/ Descriptions

TO-92

PNP

Silicon PNP transistor in a TO-92 Plastic Package.


/ Features

High current, Low voltage.

/ Applications

500mA

General purpose amplifier and switch requiring collector currents up to 500 mA.

/ Equivalent Circuit**/ Pinning**

PIN1	Collector	PIN 2	Base	PIN 3	Emitter
------	-----------	-------	------	-------	---------

/ h_{FE} Classifications & Marking

See Marking Instructions.

2N4403

Rev.F Sep.-2016




ET

Parameter	Symbol	Rating
Collector to Base Voltage	V_{CBO}	-40
Collector to Emitter Voltage	V_{CEO}	-40
Emitter to Base Voltage	V_{EBO}	-5.0
Collector Current - Continuous	I_C	-600
Collector Power Dissipation	P_C	625
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200
Junction Temperature	T_j	150
Storage Temperature Range	T_{stg}	-55 15


Parameter	Symbol	Test Conditions	Min	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C = -0.1mA$ $I_E = 0$	-40	V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C = -1.0mA$ $I_B = 0$	-40	V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E = -0.1mA$ $I_C = 0$	-5.0	V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = -40V$ $I_E = 0$		mA

/ Electrical Characteristic Curve




T O - 92

Unit: mm mm



/ Marking Instructions



BR

N4403


Note:

BR: Company Code.

N4403: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5	10±1 sec.	Temp.:270±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ Packaging SPEC.

/ BULK