


TO-92 NPN Silicon NPN transistor in a TO-92 Plastic Package.

2N5401
 High voltage, complementary Pair with 2N5401.

General purpose high voltage amplifier.




PIN1 Collector PIN 2 Base PIN 3 Emitter

h_{FE} Classifications Symbol	A	B	C
h_{FE} Range	50~150	100~300	200~400


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	180	V
Collector to Emitter Voltage	V_{CEO}	160	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current - Continuous	I_C	600	mA
Base Current - Continuous	I_B	300	mA
Collector Power Dissipation	P_C	625	mW
Junction Temperature	T_J	150	
Storage Temperature Range	T_{stg}	-55~150	


Parameter	Symbol	Test Conditions	 RPG°	Unit
-----------	--------	-----------------	---	------



T0-92

Unit: mm





BR

N5551

A: h_{FE}


Note:

BR: Company Code.

N5551: Product Type Code.

A: h_{FE} Classifications Symbol.

****: Lot No. Code, code change with Lot No.



Note:

- 1

25 150

60 90sec;
- 2

255±5

5±0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255±5

, Duration:5±0.5sec.
3. Cooling Speed: 2~10

/sec.

270±5

10±1 sec.

Temp.:270±5

Time:10±1 sec

/ BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195
	1,000	10	10,000	10	100,000	135×190	237×172×102	560×245×375

/ AMMO

Package Type	Units					Dimension (unit mm3)	
	Units/tape /	Tape/Inner Box /	Rows/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Inner Box	Outer Box
TO-92	3,000	1	120	10	30,000	328×230×42	480×346×235 547×407×268