

“Y / Descriptions

SOT-323 PNP Silicon PNP transistor in a SOT-323 Plastic Package.


• È / Features

2SC1741W
Large I_c low $V_{ce(sat)}$, complementary pair with the 2SC1741W.

v / Applications

Medium power amplifier applications.

∏ ~ ã ÷ / Equivalent Circuit



ã / ũ / Pinning



PIN1 Emitter PIN 2 Base PIN 3 Collector

±. H Ñ / Marking

h_{FE} Classifications Symbol	P	Q	R
h_{FE} Range	82~180	120~270	180~390
Marking	HHP	HHQ	HHR


绝对最大额定值 (Ta=25℃)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-40	V
Collector to Emitter Voltage	V_{CEO}	-32	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	

电 气 特 性 (Ta=25℃)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C = -100\mu A$	-40			V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C = -1.0mA$	-32			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E = -100\mu A$	-5.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = -20V$			-1.0	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB} = -4.0V$			-1.0	μA
DC Current Gain	h_{FE}	$V_{CE} = -3.0V$ $I_C = -10mA$	82		390	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -100mA$ $I_B = -10mA$			-0.4	V
Transition Frequency	f_T	$V_{CE} = -5.0V$ $I_E = 20mA$ $f = 100MHz$		200		MHz
Collector output capacitance	C_{ob}	$V_{CB} = -10V$ $I_E = 0$ $f = 1.0MHz$		7.0		pF


Electrical Characteristic Curve




⌘ È Ò Ì f / Package Dimensions

SOT-323

单位; mm



1. 标记 / Marking Instructions



H

H

P h_{FE}


Note:

H: Company Code.

H: Product Type.

P h_{FE} Classifications Symbol

Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0luhh,



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

Notices