

/ Descriptions

WR0459 ММ SQS æ Ñ ç s ll 1 Silicon PNP transistor in a TO-126 Plastic Package.


/ Features

лъ 5VF4495 Ъ
Complementary pair with 2SC1162.

/ Applications

тэъ Æ I ' ò º
Low frequency power amplifier applications.

/ Equivalent Circuit



/ Pinning




PIN1 χ Emitter PIN 2 χ Collector PIN 3 χ Base

/ h_{FE} Classifications & Marking

h _{FE} Classifications Symbol	B	C	D
h _{FE} Range	60 120	100 200	160 320

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-35	V
Collector to Emitter Voltage	V_{CEO}	-35	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-2.5	A
Peak Collector Current	I_{CP}	-3.0	A
Collector Power Dissipation	P_C	750	mW
Collector Power Dissipation	$P_C(T_c=25^\circ C)$	10	W
Junction Temperature	T_j	150	


/ **Electrical Characteristic Curve**



/ Package Dimensions


T□-126

单位: mm



Dimensions in Millimeters			Dimensions in Millimeters		
Symbol	Min	Max	Symbol	Min	Max
A	7.8	8.2	a1	0.66	0.86
B	10.6	11.0	E	2.1	2.5
B1	3.6	4.0	C	2.7	2.9
R	2.9	3.3	C1	1.57	1.77
b	14	16	c	0.3	0.6
b1	1.9		a	1.37	
E1	2.1	2.5	r	120°	

/ Marking Instructions



” X	
EU X	ꯏ ꯚ ꯍ ꯓ
D: 48 X	ꯏ ꯚ ꯍ ꯓ
E=	ꯏ k _{IH} ꯍ ꯓ
---- X	ꯏ ꯚ ꯍ ꯓ ꯍ ꯚ ꯍ ꯓ ꯍ ꯚ ꯍ ꯓ
Note:	
BR:	Company Code
A715:	Product Type.
B:	h _{FE} Classifications Symbol
****:	Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)

