


Silicon PNP transistor in a TO-92 Plastic Package.

High total dissipation, high h_{FE} and low $V_{CE(sat)}$.


Output stage of portable radio and cassette type tape recorder, general purpose applications.



PIN1 Base PIN 2 Collector PIN 3 Emitter


h_{FE} Classifications Symbol	M	L	K
h_{FE} Range	90~180	135~270	200~400


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-30	V
Collector to Emitter Voltage	V_{CEO}	-25	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-700	mA
Base Current – Continuous	I_B	-150	mA
Collector Power Dissipation	P_C	600	mW
Junction Temperature	T_J	150	
Storage Temperature Range	T_{stg}	-55 150	



T0-92

Unit: mm





h_{FE}

Note:

BR: Company Code.

A952: Product Type Code.

M: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

,

Time:60~90sec.
- 2.Peak Temp.:255 5

,

Duration:5 0.5sec.
3. Cooling Speed: 2~10

,

/sec.

270 5

10 1 sec.

Temp:270±5

Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)		
	只 袋	袋 盒	只 盒	盒 箱	只 箱	袋	盒	箱

/ AMMO

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)	
	只 纸带	纸带 盒	纸带层 盒	盒 箱	只 箱	盒	箱
							小箱 , 大箱