

/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.

/ Features

High f_T .

/ Applications

High frequency general-purpose amplifier applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	2	3	4
h_{FE} Range	40 80	60 120	90 180
Marking	HJ2	J3H	HJ4







/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	25	V
Collector to Emitter Voltage	V_{CEO}	20	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current	I_C	30	mA
Collector Power Dissipation	P_C	150	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=10V$ $I_E=0$			0.1	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB}=3.0V$ $I_C=0$			0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=6.0V$ $I_C=1.0mA$	40		180	
Transition Frequency	f_T	$V_{CE}=6.0V$ $I_C=4.0mA$	450	750		MHz
Noise Figure	NF	$V_{CE}=6.0V$ $I_C=1.0mA$ $f=100MHz$		2.2		dB
Collector-base parameter	$r_{bb'Cc}$	$V_{CB}=6.0V$ $I_C=1.0mA$ $f=31.9MHz$			19	ps
Gate Dissipation	P_G	$V_{CE}=6.0V$ $I_C=1.0mA$ $f=100MHz$		28		dB
Reverse transfer capacitance (Common emitter)	C_{re}	$V_{CB}=6.0V$ $f=1.0MHz$		0.6	0.9	pF


/ **Electrical Characteristic Curve**




/ Package Dimensions

SOT-23

单位: mm



/ Marking Instructions



H

J

2 h_{FE}


Note:

H Company Code

J Product Type Code

2 h_{FE} Classifications Symbol Code

() /



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices