

/ Descriptions

TO-220 NPN Silicon NPN transistor in a TO-220 Plastic Package.


/ Features

Low saturation voltage, excellent current dependence of h_{FE} , short switching time.


/ Applications

Various inductance lamp drivers for electrical equipment, inverters converters, power amp, high-speed switching.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Q	R	S
h_{FE} Range	70~140	100~200	140~280







/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	80	V
Collector to Emitter Voltage	V_{CEO}	60	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	5.0	A
Collector Current - Continuous	I_{CP}	7.0	A
Collector Power Dissipation	$P_C (T_C=25)$	30	W
Junction Temperature	T_J	150	
Storage Temperature Range	T_{stg}	-55~150	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=1mA$ $R_{BE}=$	60			V
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=1mA$ $I_E=0$	80			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_C=1mA$ $I_C=0$	5			V
Emitter Cut-Off Current	I_{CBO}	$V_{CB}=40V$ $I_E=0$			100	A
Collector Cut-Off Current	I_{EBO}	$V_{EB}=4V$ $I_C=0$			100	A
DC Current Gain	h_{FE}	$V_{CE}=2V$ $I_C=1A$	70		280	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=2.5A$ $I_B=0.125A$			0.4	V
Transition Frequency	f_T	$V_{CE}=5V$ $I_E=1A$		100		MHz
Turn-On Time	t_{on}	See specified Test Circuit		0.1		s
Storage Time	t_{stg}			0.5		s
Fall Time	t_f			0.1		s


/ Electrical Characteristic Curve




/ Package Dimensions

单位: mm

TO-220



/ Marking Instructions



BR

C3253

Q: h_{FE}

Note:


BR: Company Code

C3253: Product Type.

Q: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type	Units				Dimension (unit mm ³)
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	