

/ Descriptions



Silicon NPN transistor in a TO-3P Plastic Package.

/ Features

High voltage, high speed switching, High reliability.

/ Applications

Relay drivers, high-speed inverters, general high-current switching applications.

/ Equivalent Circuit**/ Pinning**


PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
-----------	--------	--------	------


/ **Electrical Characteristic Curve**



/ **Package Dimensions**



/ **Marking Instructions**




Note:

BR: Company Code.

C3320: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255 5

, Duration:5 0.5sec.
3. Cooling Speed: 2~10

/sec.

/ Resistance to Soldering Heat Test Conditions

270 5 10 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ TUBE

Package Type	Units					Dimension		(unit mm ³)
								x x

/ Notices