

Rev.I Jun.-2024

5 é

: 5 .> // x 9 ² ... ~ož Voltage Regulator in a TO-92 Plastic Package.


□ a

€ 19 ² ... ~k ý ß v ä S' Ä — ½ ' y ? è ' òž
 3-Terminal regulators ,output current up to 100 mA, internal thermal overload protection and short-circuit limiting.


Đ ÷

9 ² ... ~ož
 Voltage Regulator.

Ã W] Ô · € Đ Ô ·



• Ô - æ



PIN1 y IN

PIN 2 y GND

PIN 3 y OUT

, M V

• - ~ a ¢ož

See Marking Instructions.


表 1 主要电气特性

Parameter	Symbol	Rating	Unit
Input voltage	V_I	35	V
Output current	I_O	100	mA
Operating temperature range	T_{OPR}	-40 ~ 125	
Power Dissipation	P_D	500	mW
Storage temperature range	T_{stg}	-65 ~ 150	

表 2 典型性能指标

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output voltage	V_O	$I_O \leq 40mA$ $T_j=25$	11.5	12	12.5	V
		$I_O=1mA$ to 40mA $V_I=14V$ to 27V	11.4	12	12.6	V
		$I_O=1mA$ to 70mA $V_I=19V$	11.4	12	12.6	V
Input regulation	ΔV_O	$V_I=14.5V$ to 27V $T_j=25$		55	250	mV
		$V_I=16V$ to 27V $T_j=25$		49	200	mV
Ripple rejection	RR	$V_I=15V$ to 25V $T_j=25$ $f=120Hz$	37	42		dB
Output regulation	ΔV_O	$I_O=1mA$ to 100mA $T_j=25$		22	100	mV
		$I_O=1mA$ to 40mA $T_j=25$		13	50	mV
Output noise voltage	V_N	$f=10Hz$ to 100KHz $T_j=25$		70		μV
Dropout voltage	V_D	$T_j=25$		1.7		V
Bias current	I_Q	$T_j=25$		4.3	6.5	mA
		$T_j=125$			6.0	mA
Bias current change	ΔI_Q	$V_I=16V$ to 27V			1.5	mA
		$I_O=1mA$ to 40mA			0.1	mA


Ô ? d • Ž ¢




$$\emptyset \propto \rightarrow \mathbb{C}$$

T0-92

Unit: mm



, M y f



^a ϕ y
BR y , [W A
78L12 y D } ° Z
 y ÿ D Z W A k š ÿ D Z J

Note:
BR: Company Code
78L12: Product Type
****: Lot No. Code, code change with Lot No

