

“Y / Descriptions

SOT-323 NPN Silicon NPN transistor in a SOT-323 Plastic Package.


• È / Features

Small feedback capacitance, low noise figure, high f_T .

v / Applications

2GHz
Low noise small signal amplifiers up to 2 GHz.

∏ ã ß / Equivalent Circuit



ã / ũ / Pinning



PIN1 Emitter PIN 2 Base PIN 3 Collector





£. ¤ Ñ / Marking

h_{FE} Range	65~150
Marking	HWV2

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	10	V
Emitter to Base Voltage	V_{EBO}	2.5	V
Collector Current - Continuous	I_C	50	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=1.0mA$ $I_B=0$	10			V
Collector cut-off current	I_{CES}	$V_{CE}=20V$ $V_{BE}=0$			100	μA


电 气 特 性 曲 线 / Electrical Characteristic Curve




⊂ É Ò Ľ ģ / Package Dimensions

SOT-323

单位: mm



1. 标记 / Marking Instructions



H


WV2

Note:

H: Company Code.

WV2: Product Type.

Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0luhh,



Note:

- | | | | |
|---|----------|-------------|---|
| 1 | 25 ~ 150 | 60 ~ 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

Notices