

BR2N7002K2Q



DATA SHEET

--	--	--


/ Descriptions

/ Features


2KV AEC-Q101

/ Applications

/ Equivalent Circuit



/ Pinning



/ Marking

--	--



	(℃)		
	(℃)		
			℃
		~	℃
	θ		℃
	$\theta \leq$		

-

/ Electrical Characteristics(Ta=25)

—		Ω				
—						



/ Electrical Characteristic Curve








Figure 4 On-Resistance Variation with Temperature






/ Electrical Characteristic Curve



BR2N7002K2Q




/ Package Dimensions




Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
L	2.2	2.7	C	1.30Max	
1.20			0.45	0.65	0.90
0.20			A	1.50	0.05
0.10			B	2.70	3.10
0.15			P	0.35	0.35
0.35			Q	0.35	0.35

/ Marking Instructions



() / Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 、预热温度 ~ °C，时间 ~ °C
- 、峰值温度 ± °C，时间持续为 ± °C ±
- 、焊接制程冷却速度为 ~ °C °C

/ Resistance to Soldering Heat Test Conditions

温度： ± °C 时间： ± °C

/ Packaging SPEC.

卷盘包装

封装形式	包装数量					包装尺寸		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205

/ Notices