

/ Descriptions

Silicon NPN transistor in a SOT-323 Plastic Package.


/ Features

Low C_{ob}, Qualified to AEC-Q101 Standards for High Reliability, HF Product.


/ Applications

General amplifier, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h _{FE} Classifications Symbol	Q	R	S
h _{FE} Range	120~270	180~390	270~560
Marking	QBQ	QBR	QBS


Parameter

/ Electrical Characteristic Curve



BR2SC4081WQ

/ Marking Instructions




Note:

Q: Automobile halogen-free product Code

B: Product Type

Q: h_{FE} Classifications Symbol

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255 5

5 0.5sec;

2.Peak Temp.:255 5 , Duration:5 0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-323	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205

/ Notices