

Rev.A May.-2023



SOT-323

Silicon Diode in a SOT-323 Plastic Package.

AEC-Q101

Schottky diodes, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

High Conductance Ultra Fast Diode, Meet the stringent requirements of automotive applications.






PIN: See Equivalent Circuit.

Model	BRBAT54WAQ	BRBAT54AWAQ	BRBAT54CWAQ	BRBAT54SWAQ
Marking	QL4P	QL42	QL43	QL44

Rev.A May.-2023

Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_{RRM}	30	V
Average Rectified Forward Current	$I_{F(AV)}$	300	mA
Non-repetitive Peak Forward Surge Current	I_{FSM}	1	A
Power Dissipation	P_{tot}	230	mW





Q

L4P

Note:

Q: Automobile halogen-free product Code

L4P: Product Type

Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm³)	
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒