

/ Revised record




F	2017-4				
G	2020-5-18	1			
A	2022-2-21	all	BR Q AEC-Q101 H Q 245±5°C 5±0.5sec 255±5°C 5±0.5sec		

SOT-23 塑封封装 NPN 半导体三极管。Silicon NPN transistor in a SOT-23


参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Collector to Base Voltage	V_{CBO}	50	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current - Continuous	I_C	100	mA
Collector Power Dissipation	P_C	350	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55~150	°C

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=30V$ $I_E=0$			0.015	μA
DC Current Gain	h_{FE}	$V_{CE}=5.0V$ $I_C=2.0mA$	110		800	
Collector to Emitter Saturation Voltage	$V_{CE(sat)1}$	$I_C=10mA$ $I_B=0.5mA$		0.09	0.25	V
	$V_{CE(sat)2}$	$I_C=100mA$ $I_B=5.0mA$		0.2	0.6	V
Base to Emitter Saturation Voltage	$V_{BE(sat)1}$	$I_C=10mA$ $I_B=0.5mA$		0.7		V
	$V_{BE(sat)2}$	$I_C=100mA$ $I_B=5.0mA$		0.9		V
Base to Emitter Voltage	$V_{BE(on)1}$	$V_{CE}=5.0V$ $I_C=2.0mA$	0.58		0.7	V
	$V_{BE(on)2}$	$V_{CE}=5.0V$ $I_C=10mA$			0.5	V

/ Electrical Characteristic Curve




/ Package Dimensions



Dimensions In Millimeters			Dimensions In Millimeters		
Symbol	Min	Max	Symbol	Min	Max
A	1.15	1.75	A'	1.50	1.80Max
B	0.75	1.15	B'	0.90	1.20
C	0.20MIN		C'	0.25	0.30
D	7°		D'	1.70	2.10
			E1	0.85	1.05
			b	0.35	0.55

/ Marking Instructions



说明：

Q： 为汽车无卤产品标识


1E： 为型号代码

Note:

Q: Automobile halogen-free product Code

1E: Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 1、预热温度 150 ~ 200℃，时间 60 ~ 120sec;
- 2、峰值温度 255±5℃，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2 ~ 10℃/sec.

Note:

- 1.Preheating:150~200℃, Time:60~120sec.
- 2.Peak Temp.:255±5℃, Duration:5±0.5sec.
3. Cooling Speed: 2~10℃/sec.

/ Resistance to Soldering Heat Test Conditions

温度：260±5℃

时间：10±1 sec.

Temp.:260±5℃

Time:10±1 sec

/ Packaging SPEC.

卷盘包装 / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

/ Notices