

/ Descriptions

SOD-123

Zener Diode in a SOD-123 Plastic Package.

/ Features


500mW , AEC-Q101

500mW power dissipation, medium current, automated assembly processes, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications

2.4V-39V

2.4V to 39V wide zener voltage range applications, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit**/ Pinning**

PIN1:Cathode

PIN2:Anode

/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)


Parameter	Symbol	Rating	Unit
Forward Voltage (Note 2) $I_F=10\text{mA}$	V_F	0.9	V
Power Dissipation(Note 1)	P_D	500	mW
Typical Thermal Resistance Junction to Ambient(Note 1)	$R_{\theta JA}$	305	$^{\circ}\text{C}/\text{W}$
Junction and Storage Temperature Range	T_j, T_{stg}	-65 150	$^{\circ}\text{C}$

/ Electrical Characteristics(Ta=25)

Type Number	Marking Code	Zener Voltage Range				Maximum Zener Impedance			Maximum Reverse Current	
		$V_Z @ I_{ZT}$			I_{ZT}	$Z_{ZT} @ I_{ZT}$	$Z_{ZK} @ I_{ZK}$	I_{ZK}	I_R	@ V_R
		Nom (V)	Min (V)	Max (V)	mA	Ω		mA	μA	V
BRBZT52B2V4Q	Q0Z	2.4	2.35	2.45	5	94	564	1	45	1
BRBZT52B2V7Q	Q1Z	2.7	2.65	2.75	5	94	564	1	18	1
BRBZT52B3V0Q	Q2Z	3.0	2.94	3.06	5	89	564	1	9	1
BRBZT52B3V3Q	Q3Z	3.3	3.23	3.37	5	89	564	1	4.5	1
BRBZT52B3V6Q	Q4Z	3.6	3.53	3.67	5	84	564	1	4.5	1
BRBZT52B3V9Q	Q5Z	3.9	3.82	3.96	5	84	564	1	2.7	1
BRBZT52B4V3Q	Q6Z	4.3	4.21	4.39	5	84	564	1	2.7	1
BRBZT52B4V7Q	Q7Z	4.7	4.61	4.79	5	75	564	1	2.7	2
BRBZT52B5V1Q	Q8Z	5.1	5.00	5.20	5	56	470	1	1.8	2
BRBZT52B5V6Q	Q9Z	5.6	5.49	5.71	5	27	451	1	0.9	2
BRBZT52B6V2Q	QAZ	6.2	6.08	6.32	5	9	376	1	2.7	4
BRBZT52B6V8Q	QBZ	6.8	6.66	6.94	5	14	141	1	1.8	4
BRBZT52B7V5Q	QCZ	7.5	7.35	7.65	5	14	75	1	0.9	5
BRBZT52B8V2Q	QDZ	8.2	8.04	8.36	5	14	75	1	0.63	5
BRBZT52B9V1Q	QEZ	9.1	8.92	9.28	5	14	94	1	0.45	6
BRBZT52B10Q	QFZ	10	9.80	10.20	5	18	141	1	0.18	7
BRBZT52B11Q	QGZ	11	10.78	11.22	5	18	141	1	0.09	8


BRBZT52BXXXQ

/ Electrical Characteristic Curve





/ Marking Instructions



Q


0Z

Note:

Q: Automobile halogen-free product Code

0Z: Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3.Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOD-123	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices