



B	2018-4				
C	2019-3-7	1			
D	2020-11-9	1 3 4	4057 VBAT 4.158~4.242V		




BRCL3550MF /
BRCL3550MF

4.20V±1%
/ /
7V
0V
C/10
1uA
BAT-VDD

USB

BRCL3550MF USB







CHRG	1	3	
------	---	---	--




	(	GND	0
--	---	-----	---

<http://www.fsbrec.com> /








•	PIN1
3550	

Note:	
•	PIN1 Mark
3550:	Product Type Code.
****:	Lot No. Code, code change with Lot No.



Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

2

245 5

5 0.5sec;

3

2 10 /sec.
- 1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245 5 , Duration:5 0.5sec.

3. Cooling Speed: 2~10 /sec.

260 5

10 1 sec.

Temp.:260 5

Time:10 1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box	Outer Box
SOT23-5/6	3,000	10	30,000	4	120,000	7" ×8	210×205×205	445×230×435