


5sec

A	2021.07.21	All	AOS-AON6242		
B	2021.09.02	2	RDSON@10V	3.0mR	

Q
AEC-Q101

A 2022-7-2 all , Q 245±
5°C 5±0.5sec



/ Descriptions

PDFN5x6 N-Channel MOSFET in a PDFN5x6 Plastic Package .

/ Features

AEC-Q101

Low $R_{DS(ON)}$ to minimize conductive loss; low Gate Charge for fast switching; Low Thermal resistance; Qualified to AEC-Q101 Standards for High Reliability; HF Product.

/ Applications


MB/NB/UMPC/VGA

Buck


—

Battery Management, High Frequency Point-of-Load Synchronous Buck Converter for MB/NB/UMPC/VGA, Networking DC-DC Power System, Load Switch, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



PIN1、2、3: S PIN4: G PIN5、6、7、8: D

Pin	极性
1	S
2	S
3	S
4	G
5	D
6	D
7	D
8	D


/ Marking

见印章说明。See Marking Instructions.


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=30V$ $R_L=1.5\ \Omega$ $R_{GEN}=3\ \Omega$		13		ns
Turn-On Rise Time	t_r			4		
Turn-Off Delay Time	$t_{d(off)}$			47		
Turn-Off Fall Time	t_f			6.5		


/ Electrical Characteristic Curve



/ Electrical Characteristic Curve




/ Package Dimensions



Rev.00 201812

/ Marking Instructions



BR


Q

035N06S

Note

BR	Company Code
Q:	Automobile halogen-free product Code
035N06S	Product Type
****:	Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1. Preheating: 150~200 , Time: 60~120sec.
2. Peak Temp.: 255 ± 5 , Duration: 5 ± 0.5sec.
3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 ± 5 10 ± 1 sec. Temp.: 260±5°C Time: 10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
PDFN5 × 6	5000	2	10000	6	60000	13" × 12	360 × 360 × 50	380 × 335 × 366

/ Notices