







/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250 A$	30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V$ $V_{GS}=0V$			1	A
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 0.1	A
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250 A$	1.0	1.9	2.5	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=20A$		8	9	m
		$V_{GS}=4.5V$ $I_D=10A$		12	15	m
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$ $I_S=1A$			1.2	V
Input Capacitance	C_{iss}	$V_{DS}=15V$ $V_{GS}=0V$ $f=1.0MHz$		845		pF
Output Capacitance	C_{oss}			135		
Reverse Transfer Capacitance	C_{rss}			105		
Gate resistance	R_g	$V_{GS}=0V$ $V_{DS}=0V$ $f=1MHz$		2.9		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$ $V_{DS}=15V$ $I_D=17A$		22		nC
Total Gate Charge	$Q_{g(4.5V)}$			10		
Gate Source Charge	Q_{gs}			4.7		
Gate Drain Charge	Q_{gd}			4		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=15V$ $R_L=0.75$ $R_{GEN}=3$		6.5		ns
Turn-On Rise Time	t_r			2.5		
Turn-Off Delay Time	$t_{d(off)}$			22.5		
Turn-Off Fall Time	t_f			3		

/ Electrical Characteristic Curve




/ Electrical Characteristic Curve



/ Package Dimensions

PDFN3X3A-8L


Unit:mm



Rev.00 202011



/ Marking Instructions



BR

Q

080N03

Note:


BR: Company Code

Q: Automobile halogen-free product Code

080N03: Product Type Code

****: Lot No. Code, code change with Lot No

() /



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ **Resistance to Soldering Heat Test Conditions**

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ **Packaging SPEC.**

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
PDFN3×3A-8L	5,000	2	10,000	6	60,000	13 ×12	360×360×50	380×335×366

/ **Notices**