

A	2022.2.12	ALL	AOS-AOD294A		
			Q	AEC-Q101	
A	2022-6-22	all		Q	

塑封封装 沟道场效应管。



$DS(on)$ 小，门电荷低， r_{ss} 小，开关速度快，符合

标准高可靠性要求，无卤产品。

! & 077(93 93(96)93 1

/ Absolute Maximum Ratings($T_a=25^\circ\text{C}$)

		°C		
			±	
		°C		
				°C
	≧	θ		°C
		θ		

/ Electrical Characteristics(Ta=25)

[illegible]

/ Electrical Characteristics(Ta=25)

		Ω Ω				

/ Electrical Characteristic Curve








Figure 5: On-Resistance vs. Gate-Source Voltage

Figure 6: Body-Diode Characteristics

/ Electrical Characteristic Curve



/ Package Dimensions





单位: mm

Dimensions in Millimeters				Dimensions in Millimeters			
Symbol	Min	Max	Symbol	Min	Max	Symbol	Min
A	2.25	2.20	A	2.40	2.40	P	5.95
B	0.95	0.95	e1	2.24	2.24		
C	0.90	0.90	D	6.45	6.45	L3	0.45
D	0.55	0.55	D1	6.75	6.75		
E	9.85	9.85	L3	0.45	0.45		
	2.00	2.00		0.45	0.45		
	0.60	0.90		0.55	0.55		
	0.99	0.99		0.2	1.70		

T0-252

/ Marking Instructions





() / Temperature Profile for IR Reflow Soldering(Pb-Free)

$\pm$

$^{\circ}\text{C}$

$\pm$

$^{\circ}\text{C}$

$\pm$

$^{\circ}\text{C}$

$\pm$

/ Resistance to Soldering Heat Test Conditions

$\pm$ $^{\circ}\text{C}$

$\pm$

$^{\circ}\text{C}$

/ Packaging SPEC.

' &) & * 封装形式	2	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	8 %包装数量 Units/Inner Box 只/盒	Inner Boxes/Outer Box	+ %	% 包装尺寸	, %
-------------------	---	--------------------	-------------------------	-----------------------------------	-----------------------	-----	--------	-----