

BRES36VL1B2SB

Rev.A Dec.-2024



/ Descriptions

SOD-323 Plastic Package 1-Line,Bi-directional , ESD Protection Diode.

/ Features

/ Applications

Suitable for cellular phones audio,MP3 players, Digital cameras, Portable devices, mobile telephone and other users.



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Peak Pulse Power($t_p = 8/20\mu s$)	P_{PK}	320	W
Peak Pulse Current($t_p = 8/20\mu s$)	I_{PP}	5	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	
Junction temperature	T_J	-55~+150	
Storage Temperature	T_{STG}	-55~+150	

/ Electrical Characteristics($T_a=25^\circ C$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse maximum working voltage	V_{RWM}				36	V
Reverse leakage current	I_R	$V_{RWM} = 24V$			1	μA
Reverse breakdown voltage ¹⁾	V_{BR}	$I_T=1mA$	40			V
Clamping voltage ²⁾	V_{CL}	$I_{PP} = 1A \quad t_p = 8/20\mu s$			60	V
		$I_{PP} = 5A \quad t_p = 8/20\mu s$			75	V
Junction Capacitance	C_J	$V_R = 0V \quad f = 1MHz$		15	20	pF


Notes:

1) V_{BR} is measured with a pulse test current I_T at an ambient temperature of $25^\circ C$.


2) Non-repetitive current pulse, according to IEC61000-4-5.

/ Electrical Characteristic Curve(Ta=25)


**Fig.1 ESD Clamping Voltage Screenshot
Positive 8 kV Contact perIEC61000-4-2**



**Fig.2 ESD Clamping Voltage Screenshot
Negative 8 kV Contact perIEC61000-4-2**




/ Package Dimensions



1. CALL 2. ANSWER 3. P.N.

S - 323


/ Marking Instructions



Note:

Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245 5

5 0.5sec;

2.Peak Temp.:245 5 , Duration:5 0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOD-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices