

BRMMBD4148Q/SEQ/CCQ/CAQ

Rev.A Aug.-2022



DATA SHEET

--	--	--	--	--	--

F

描述 / Descriptions

SOT-23
Silicon Diode in a SOT-23 Plastic Package.


特征 / Features

AEC-Q101
Fast Switching, High Conductance, Qualified to AEC-Q101 Standards for High Reliability, HF Product.


用途 / Applications

Small signal diode, Meet the stringent requirements of automotive applications.

内部等效电路 / Equivalent Circuit



引脚排列 / Pinning



PIN: See Equivalent Circuit.


印章代码 / Marking

Type	BRMMBD4148Q	BRMMBD4148SEQ	BRMMBD4148CCQ	BRMMBD4148CAQ
Marking	Q5H	QD4	QD5	QD6




Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_{RRM}	100	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0S)$	1.0	A
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0\mu S)$	2.0	A
Power Dissipation	PC	350	mW
Thermal Resistance, Junction to Ambient	R_{JA}		$^{\circ}C/W$
Junction Temperature	T_j	150	$^{\circ}C$
Storage Temperature			

电参数曲线图 / Electrical Characteristic Curve




外形尺寸图 / Package Dimensions



Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
L	2.2	2.7	C	1.30Max	
1.20			10.45	0.65	0.90
0.20			0.5	1.50	0.05
0.10			12.70	3.10	0
				0.20MIN	
	0.85	1.05		7°	
	0.35	0.55			

印章说明 / Marking Instructions



Note:

5H: Product Type



回流焊温度曲线图(无铅) / Temperature Profile for IR Reflow Soldering(Pb-Free)