

/ Descriptions

TO-247



Insulated-Gate Bipolar Transistor in a TO-247 Plastic Package.

/ Features

650V 100A

 $V_{CE(SAT)} = 1.60V(\text{typ.}) @ V_{GE} = 15V, I_C = 100A$ **/ Applications**

Solar Converters, Uninterrupted Power Supply, Welding Converters, Mid to High Range Switching Frequency Converters.

/ Equivalent Circuit**/ Pinning****/ Marking**

See Marking Instructions.

/ Absolute Maximum Ratings($T_a=25$)

Parameter		Symbol	Rating	Unit
Collector-Emitter Voltage		V_{CES}	650	V
Gate-Emitter Voltage		V_{GES}	± 30	V
Continuous Collector Current	$T_C=25$	I_C	200	A
	$T_C=100$		100	A
Pulsed Collector Current , Limited by T_{Jmax}		I_{CM}	400	A
Continuous Diode Forward Current	$T_C=25$	I_F	150	A
	$T_C=100$		75	A
Power Dissipation	$T_C=25$	P_D	536	W
Operating Junction Temperature Range		T_J	-40 to +175	
Storage Temperature Range		T_{STG}	-55 to +175	
Maximum Temperature for Soldering		T_L	260	
Maximum Junction-to-Ambient		$R_{\theta JA}$	40	/W
Maximum IGBT Junction-to-Case		$R_{\theta JC}$	0.26	/W
Maximum Diode Junction-to-Case		$R_{\theta JC}$	1.26	/W


/ Electrical Characteristics($T_c=25$)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Collector-Emitter Breakdown Voltage	BV _{CES}	I _C =1.0mA, V _{GE} =0V		650			V
Zero Gate Voltage Collector current	I _{CES}	V _{CE} =650V, V _{GE} =0V				10	uA
Gate-Emitter Leakage Current	I _{GES}	V _{CE} =0V, V _{GE} = ±20V				± 200	nA
Gate-Emitter Threshold Voltage	V _{GE(th)}	V _{CE} =V _{GE} , I _C =1.0mA		4.3	5.3	6.3	V
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V _{GE} =15V, I _C =100A	T _J =25		1.60	1.95	V
			T _J =125		1.87		
			T _J =175		2.04		
Total Gate Charge	Q _g	V _{GE} =15V, V _{CC} =520V I _C =100A			405		nC
Gate to Emitter Charge	Q _{ge}				72		
Gate to Collector Charge	Q _{gc}				189		




/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GE}=15V$, $V_{CC}=400V$ $I_C=100A$, $R_G=5\Omega$ Inductive Load	$T_J=25$		40		ns
			$T_J=175$		50		ns
Turn-On Rise Time	t_r		$T_J=25$		174		ns
			$T_J=175$		183		ns
Turn-Off Delay Time	$t_{d(off)}$		$T_J=25$		230		ns
			$T_J=175$		403		ns
Turn-Off Fall Time	t_f		$T_J=25$		136		ns
			$T_J=175$		177		ns
Turn-On Energy	E_{on}		$T_J=25$		4.89		mJ
			$T_J=175$		5.06		mJ
Turn-Off Energy	E_{off}		$T_J=25$		3.71		mJ
			$T_J=175$		5.01		mJ
Total Switching Energy	E_{ts}		$T_J=25$		8.6		mJ
			$T_J=175$		10.07		mJ
Input Capacitance	C_{ies}	$V_{GE}=0V$, $V_{CE}=25V$ $f=1MHz$			7220		pF
Output Capacitance	C_{oes}				369		pF
Reverse Transfer Capacitance	C_{res}				198		pF
Short Circuit Safe Operation Area	SCSOA	$V_{GE}=15V$, $V_{CC} \leq 400V$, $T_{J,start} \leq 25$		5			μs
Diode Forward Voltage	V_F	$I_F=40A$	$T_J=25$		1.35		V
Diode Reverse Recovery Time	T_{rr}	$V_R=400V$, $I_F=75A$ $dI_F/dt=200$ $A/\mu s$ $T_C=25$	$T_J=25$		136		ns
			$T_J=175$		183		
Diode Reverse Recovery Charge	Q_{rr}		$T_J=25$		430		μC
			$T_J=175$		670		
Diode Peak Reverse Recovery Current	I_{rm}		$T_J=25$		6.3		A
			$T_J=175$		8.5		




/ Electrical Characteristic Curve




/ Electrical Characteristic Curve




/ Electrical Characteristic Curve



/ Electrical Characteristic Curve



/ Marking Instructions



BR

PGB100N65AHA

Note:

BR:

Company Code


PGB100N65AHA:

Product Type Code

****:

Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 °C , Time:60~90sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 °C , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 °C /sec.

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-247	30	15	450	5	2250	520×44×6	580×158×55	595×300×178

/ Notices

All information provided in this document is subject to legal disclaimers.