

/ Descriptions

TO-220 Voltage Regulator in a TO-220 Plastic Package.


/ Features

1A,
3-Terminal regulators ,output current up to 1A, internal thermal overload protection and short-circuit limiting.


/ Applications

Voltage Regulator.

/ / Equivalent Circuit or Application Circuit



/ Pinning



PIN1 IN PIN 2 GND PIN 3 OUT

/ Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Input voltage	V_I	35	V
Operating Junction Temperature Range	T_{OPR}	0 125	
Storage temperature range	T_{stg}	-65 150	



Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output voltage	V_O	$T_j=25$	4.8	5.0	5.2	V
		$V_i=7V-20V$, $I_o=5mA-1A$ $P_o \leq 15W$	4.75	5.0	5.25	V

Load Regulation V_o $T_j=25$

/ Package Dimensions


T0-220

单位: mm



Symbol	Dimensions in Millimeters		Symbol	Dimensions in Millimeters	
	Min.	Max.		Min.	Max.
A	9.8	10.2	C	1.2	1.4
R	3.56	3.64	B	6.3	6.7
b	12.6	13.6	D1	9.0	9.4
b1	9.6	10.6	C1	2.2	2.6
a	1.22	1.32	a1	0.7	0.9
E	2.34	2.74	c	0.4	0.6
Q2	1.25	1.45	C2	4.3	4.7

/ Marking Instructions



BR

L7805


Note:

BR: Company Code.

L7805: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270 5 10 1 sec. Temp:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension		(unit mm3)

/ TUBE

Package Type	Units					Dimension		(unit mm3)