

**5 é /P**

9 5: .> // x 6 4 6 ! - } â 'ož Silicon PNP transistor in a SOT-89 Plastic Package.

α a /E



ó 9 äož

High voltage.

Đ ÷ /A

ä 9 O ò èož

High voltage control circuit.

Ã w] Ô · /E**• Ů - æ /E**

PIN1 y Base

PIN 2 y Collector

PIN 3 y Emitter

, M V /M

Marking	H4D *
---------	-------



Ã a ? d I ;)


@ f Parameter	... Z Symbol	f > Rating	% y Unit
Collector to Base Voltage	V _{CBO}	-400	V
Collector to Emitter Voltage	V _{CEO}	-400	V
Emitter to Base Voltage	V _{EBO}	-5.0	V
Collector Current - Continuous	I _C	-300	mA
Collector Power Dissipation	P _C	500	mW
Junction Temperature	T _j	150	
Storage Temperature Range	T _{stg}	-55 150	

Ô4i × ? d I ;)

@ f Parameter	... Z Symbol	y j Ú ^ Test Conditions	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Collector to Base Breakdown Voltage	V _{CBO}	I _C =-100 A I _E =0	-400			V
Collector to Emitter Breakdown Voltage	V _{CEO}	I _C =-1.0mA I _B =0	-400			V
Emitter to Base Breakdown Voltage	V _{EBO}	I _E =-100 A I _C =0	-5.0			V
Collector Cut-Off Current	I _{CBO}	V _{CB} =-300V I _E =0			-0.1	A
Emitter Cut-Off Current	I _{CES}	V _{CE} =-400V V _{BE} =0			-1	A
Emitter Base Cut-Off Current	I _{EBO}	V _{EB} =-4.0V I _C =0			-0.1	A
DC Current Gain	h _{FE(1)}	V _{CE} =-10V I _C =-10mA	80		300	
	h _{FE(2)}	V _{CE} =-10V I _C =-1.0mA	70			
	h _{FE(3)}	V _{CE} =-10V I _C =-100mA	40			
Collector to Emitter Saturation Voltage	V _{CE(sat) (1)}	I _C =-10mA I _B =-1.0mA			-0.2	V
	V _{CE(sat) (2)}	I _C =-50mA I _B =-5.0mA			-0.3	V
Emitter to Base Saturation Voltage	V _{BE(sat)}	I _C =-10mA I _B =-1.0mA			-0.75	V
Transition Frequency	f _T	V _{CE} =-5.0V I _C =-10mA f=30MHz	50			MHz



Ô ? d • Ž ¢ / 15






Ø □ =) ☎ /


SUT-89

单位: mm





, My f / M



^a ¢ y

H y , [W A

4D y ° Z W A

y Ÿ D Z W A k š Ÿ D Z J ož

Note:


H: Company Code.

4D: Product Type.

** : Lot No. Code, code change with Lot No.



šWD t...•Žč (x/)/ :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6



^ačy

- 1o• Ä ½ “ † 150 ½180 - k ž • 60 ½90sec;
- 2o• Q > “ † 245 r5 - k ž • 4 Ò 5 r0.5sec;
- 3o•D N ò i Ò 0 , † 2 ½10 - /sec.

Note:

- 1.Preheating:150~180 - , Time:60~90sec.
- 2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.
3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] T