

/ Descriptions

Surface Mount Schottky Barrier Rectifiers, Reverse Voltage 20 to 200V ,Forward Current:5.0A ,SMB package.

/ Features

Low power loss, high efficiency High forward surge current capability, Lead free in comply with EU RoHS 2011/65/EU directives, For surface mounted applications,HF Product.


/ Applications

General purpose.

/ Equivalent Circuit




/ Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size



/ Marking

See Marking Instructions.

SS52BMA~SS520BMA

Rev.A Nov.-2024

Parameter	Symbol	Rating								Unit
		SS52 BMA	SS54 BMA	SS56 BMA	SS58 BMA	SS510 BMA	SS512 BMA	SS515 BMA	SS520 BMA	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS voltage	V_{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current @ Fig.1	$I_{F AV}$	5.0								A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	100								A
Peak Forward Surge Current,1.0ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	200								A

I^2

/ Electrical Characteristic Curve

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



SS52BMA~SS520BMA

Rev.A Nov.-2024



蓝箭电子
BLUE ROCKET ELECTRONICS

DATA SHEET

/ Package Dimensions

/ Marking Instructions

SS52A

Note:


Product Type Code

Lot No. Code, code change with Lot No

Marking

Type number	Marking code
SS52BMA	SS52A
SS54BMA	SS54A
SS56BMA	SS56A
SS58BMA	SS58A
SS510BMA	SS510A
SS512BMA	SS512A
SS515BMA	SS515A
SS520BMA	SS520A

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 | 5 | 5 | 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
SMB	3,000	2	6,000	7	42,000	13 ×12	336X336X40	380X335X366

/ Notices