

5 é / Descriptions

n μ É xRK Ô Â ... v 8 â ' k F g 9 y < k 3 g v y ' k 9 3 (/ xož
Surface Mount Schottky Barrier Rectifiers, Reverse Voltage y 40V,Forward Current: 3.0A ,SMB package.

□ a / Features

z ô k ä | ä k ä 3 g ~ ... v k n μ É x k —)í D }ož
Low power loss, High efficiency, High forward surge current capability, For surface mounted applications, HF Product.


Đ ÷ / Applications

%² " (ož
General purpose.

Ã W] Ô · / Equivalent Circuit




• Ô - æ / Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size



, M V / Marking

Type number	Marking
SSL34B	SSL34

1. Absolute Maximum Ratings(Ta=25 ;)

@ f Parameter	... Z Symbol	f > Rating	% y Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	40	V
Maximum RMS voltage	V _{RMS}	28	V
Maximum DC Blocking Voltage	V _{DC}	40	V
Maximum Average Forward Rectified Current at T _c =100°C	I _{F AAV A}	3	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I _{FSM}	80	A
Typical Junction Capacitance ¹⁾	C _j	450	pF
Typical Thermal Resistance ²⁾	R _{JA}	60	/W
Operating Junction Temperature Range	T _j	-55~+150	
Storage Temperature Range	T _{stg}	-55~+150	

Note:


1) Measured at 1 MHz and applied reverse voltage of 4 V D.C.

2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

2. Electrical Characteristics(Ta=25 ;)


@ f Parameter	... Z Symbol	y i Ú ^ Test Conditions	I Rating	% y Unit
Maximum Instantaneous Forward Voltage	V _F	I _F =3.0A	0.45	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	T _a =25 T _a =100	0.3 5	mA

Electrical Characteristic Curve




Ø □ =) ☿ / Package Dimensions

SMB



, M y f / Marking Instructions



9 9 2 y ° Z W A
**** y ŷ D Z W A k š ŷ D Z J

Note:
9 9 2 y Product Type Code
**** y Lot No. Code, code change with Lot No Code

