

5 é / Descriptions

n μ É xRK Ô Â 8 â ' k F g 9 y < k 3 g v y ' k V ° S M B F / x o ž
Surface Mount Schottky Barrier Rectifier, Reverse Voltage:45V,Forward Current:5.0A,SMBF thin package.

□ ª / Features

z ô k ä | ä k ~ ... v Ý k 9 z 9 k ä È y â Â ' k 9 n μ É x k —) í D } o ž
Low power loss, high efficiency, High forward surge current capability, For use in low voltage, high frequency inverters, and polarity protection applications,For surface mounted applications,HF Product.


Đ ÷ / Applications

%² " (o ž
General purpose.


Ã W] Ô · / Equivalent Circuit



• Ů - æ / Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode



, M V / Marking

• - ~ ª ¢ o ž
See Marking Instructions.

1. Absolute Maximum Ratings(Ta=25℃ ;)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	45	V
Maximum RMS voltage	V_{RMS}	32	V
Maximum DC Blocking Voltage	V_{DC}	45	V
Maximum Average Forward Rectified Current	I_{FAV}	5.0	A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	150	A
Typical Junction Capacitance ¹	C_j	500	pF
Typical Thermal Resistance ²	R_{JA}	55	/W
Operating Junction Temperature Range	T_j	-55~+125	
Storage Temperature Range	T_{stg}	-55~+150	

Note:

1 Measured at 1 MHz and applied reverse voltage of 4 V D.C

2 P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

2. Electrical Characteristics(Ta=25℃ ;)

Parameter	Symbol	Test condition	Rating	Unit
Max Instantaneous Forward Voltage	V_F	$I_F=5.0A$	0.43	V
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	$T_j=25$	0.5	mA
		$T_j=100^{\circ}C$	20	

Electrical Characteristic Curve

Fig.1 Typical Forward Characteristic Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig.6 Typical Transient Thermal Impedance




, M y f / Marking Instructions



a ¢ y
9 2 (y ° Z W A
**** y ÿ D Z W A k š ÿ D Z J

Note:
9 2 (y Product Type Code
**** y Lot No. Code, code change with Lot No

šWD t...•Ž¢ (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6



a ¢ y

- 1o• Ä ½ “† 150 ½180 - k ž • 60 ½90sec;
- 2o• Q > “† 245 r5 - k ž • 4 Ò 5 r0.5sec;
- 3o•D N ò i Ò 0 ,† 2 ½10 - /sec.

Note:

- 1.Preheating:150~180 - , Time:60~90sec.
- 2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.
- 3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“† y 260 r5 - ž • y 10 r1 sec. Temp.:260±5 Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit /Æmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
SMBF	5,000	2	10,000	7	70,000	13 s ×12	336X336X40	380X335X366

„Đ y f / Notices